ROADPASSION

Peugeot / Citroen
RS-2945 Installation Guide

Connect to the original car host power head

Connect with the male head of the original car wire head

Pull out the USB cable

REAR: Connect with camera

Blue: Camera power supply

USB cable interface

CAN line plugged in

Manual transmission brown wire connected to reversing lights

Buckle up the antenna

Plug-in decoder, two-wire

Plug in with the video cable of the original car host

Pull out the antenna, do not ground

Connect to the video port of the original car host

Display screen line

OEM CD player

• Host diagram

13-16 Peugeot/Citroen SETTING

1	2	3	7	Car Model	8		
OFF	OFF	OFF	/	LIST and PHONE in two buttons on SW		/	/
ON	OFF	OFF	/	LIST and PHONE in one button on SW		/	/
4	5	6		Screen Size		/	/
OFF	OFF	/		800*480 7"			

Peugeot / Citroen

1 Carplay play music up and down function

2 Carplay function fairy answer and hang up

3 In the original car interface, press 2 times to switch to the AUX channel

4 Long press to switch interface, short press to call SIRI

5 Volume addition and subtraction function, original car and CARPLAY

6 Short press to switch between the original car and the installation interface, press this button on the 308 and 408 panels

All other functions are operated by the original car

iOS   Android   Mirroring   USB 媒体

*Wired/Wireless CarPlay   *Wired/Wireless Android AUTO

*Mirror Link function (Apple, Android)

*USB multimedia playback (supports lossless audio, 720P video and picture playback)

*Support original car rear view, retrofit rear view (CVBS/AHD), front view (time delay can be set) or DVR

*Support expansion and installation of 360 panorama (CVBS/AHD)

* Support audio EQ adjustment, music navigation volume adjustment separately

*Support the original car MIC (reserved to install MIC), support the automatic correction function of call cancellation and echo.

* Support original car Bluetooth call function   *Support AUX IN function, can expand digital TV

*Support wired BaiDu Car Life (requires factory setting to open, password 0301)

前视摄像头   AV in   主界面   设置

Connection and function operation instructions：

* Easy connection method of wireless CarPlay for the first time: After connecting via USB cable, follow the prompts on the mobile phone to enable wireless CarPlay.After 15 seconds, unplug the data cable and the wireless connection will be automatically connected.

1 Enter the installation settings Wireless CarPlay settings

无线CarPlay设置
无线CarPlay开关　　　　　　　　　　　**ON**
Wi-Fi 通道
在线设备列表
发现和连接设备
已配对列表

2 Click "Discover and connect devices" to pop up the CX_BT

发现和连接设备
打开手机的蓝牙并搜索
CX_BTFC4BBCEC738C，然后连接
•••••
取消

3 Open the bluetooth of the phone

蓝牙配对请求
"CARPLAY_BT_5681bc"想与您的
iPhone配对，请确认此代码显示在
"CARPLAY_BT_5681bc"上，需加在任何
配件上输入此代码。
815180
取消　　　　配对

4 Aearch for the name of CX_BT.....

使用"CARPLAY"的
CarPlay 车载？
CarPlay 车载自动向您的 iPhone 连接至
汽车内建显示屏，且在锁定时仍可访问。
使用 CarPlay 车载
以后

Note: (Apple needs to complete the Bluetooth pairing, and the WIFI on the mobile phone can be turned on to complete the wireless CarPlay connection), the next time you start the car, the connected car will be automatically connected.

Connection and function operation instructions：

* Easy connection method of wireless CarPlay for the first time: After connecting via USB cable, follow the prompts on the mobile phone to enable wireless CarPlay.After 15 seconds, unplug the data cable and the wireless connection will be automatically connected.

**1** Enter the installation settings Android Auto settings

无线Android Auto设置
Bluetooth连接 **ON**
配对 >
Bluetooth重置 >
蓝牙已配对列表 >
设备名称:CX_BTFC4BBCEC738C
蓝牙地址:FC:4B:BC:EC:73:8C

2 Click "Discover and connect devices" to pop up the CX_BT

无线Android Auto设置

打开手机的蓝牙并搜索
CX_BTFC4BBCEC738C，然后连接

....

取消

3 Connect CX_Bt... with the Android phone's Bluetooth

蓝牙配对请求
"CARPLAY_BT_5681bc"想与您的
iPhone配对，请确认此代码显示在
"CARPLAY_BT_5681bc"上。请勿在任何
配件上输入此代码。

815180

取消 | 配对

4 Enter the AUTO interface

Maps | Spotify | YT Music | Phone
Audible | iHeart Radio | Pocket Casts | Waze

Note: (Apple needs to complete the Bluetooth pairing, and the WIFI on the mobile phone can be turned on to complete the wireless CarPlay connection), the next time you start the car, the connected car will be automatically connected.

Mirroring

请插入iOS或Android设备

要信任此电脑吗?
无线或使用数据线连接后，您的设置和数据将可以从这台电脑访问。

信任　　　不信任

Click the Mirroring icon, connect the USB cable to the iPhone, and the mobile phone prompt as shown above will pop up. Click Trust to enter the screen mirroring interface.

Mirroring

请插入iOS或Android设备

In the Mirroring interface → insert the Android phone, the mobile phone will pop up the "Auto link" download box, click to download, after the download is complete, click on the browser to install, after the installation is complete, the mobile phone interface will display the Auto link icon. In the "Mirroring" interface, insert the Android phone again, and the mobile phone will pop up the "Open USB default connection box" → click "OK", after the connection, the Mirroring interface will be displayed after the connection is successful;

搜狗导航   腾讯视频   Shadowsocks   Samsung Print Servic...

Autolink

Open Autolink when this USB accessory is connected?

Use by default for this USB accessory
若要更改默认应用程序设置，请进入【设置】>【应用程序】>【默认应用程序】。

取消   确定

Click the Mirroring icon, connect the USB cable to the iPhone, and the mobile phone prompt as shown above will pop up. Click Trust to enter the screen mirroring interface.

USB Media

我的女孩

Root

1/1

00:06 ———————————————— 04:23

*Echo cancellation processing method：

音频设置

音量 >
MIC增益 ————————————
EQ >
原车MIC ON
自动消回音 >

If there is an echo on the call, you can cancel the echo as shown in the figure above, and then confirm the call echo problem.

自动消回音

请调整原车音量至74~77dBSPL,
且麦克风连接正常

确定

Inserting a U disk will automatically jump to the USB playback interface, supporting lossless audio and 720P video playback.

*Language Setting：

| ↩ 语言	※
English	▲
简体中文	
繁體中文	
Español	
Français	▼
Português	

| ↩ Language	※
Português	▲
Türk	
Deutsch	
Polski	
Русский	▼
Nederlands	

As shown in the figure above, enter the language option in the installation setting interface, and choose the right language. As shown above

*Car settings

↩ 车载设置	※
轨迹线	ON ▲
雷达	ON
加装摄像头 ｜ 原车摄像头	ON
后视 ｜ 360	OFF
AHD摄像头类型	> ▼
原车USB开关	OFF

| ↩ Advanced Features	※
Parking Guideline	ON ▲
Park Distance control	ON
Aftermarket Camera ｜ Original Camera	ON
Rear Camera ｜ 360 Panoramic	OFF
AHD Camera Type	> ▼
Factory USB Switch	OFF

The common rear view settings are as shown above. If you are installing an AHD camera, you need to enter the AHD and select the corresponding frame rate.

*Audio settings：

↩ 音频设置	※
多媒体音量	
导航音量	
通话音量	
铃声音量	
语控音量	

| ↩ Audio Settings	※
Main Volume	
Navi Volume	
In Call Volume	
Ringer Volume	
Voice Assistant Volume	

Audio settings are commonly performed as shown in the figure above, and default values are generally recommended.

*Version information and system upgrade method:

↩ 版本信息	※
关于设备	>
复位	>
恢复出厂设置	>

↩ Information	※
About Version	>
Reset	>
Factory Reset	>

View the version information as shown in the figure above, click About Device to display the current system version number information.

About Version

M: 200706V2　S: 200602V1　T: 200708V1

CX301: CX301-S3-20200623

Software Version: 2. 2. 1

Hardware: 2. 0. 0

Update

About Version

M: 200706V2　S: 200602V1　T: 200708V1

CX301: CX301-S3-20200623

Software Version: 2. 2. 1

Hardware: 2. 0. 0

Update

Import config from USB

Start importing config from USB flash drive?

Cancel　OK

① In the USB device, copy the upgrade file from the computer, after decompressing the file put the ISPBOOOT.BIN and OSU_Settings folder or update file in the root directory of the U disk;

② Insert the USB, return to the main interface→Settings→Version Information→About Device→Update→Click the corresponding file to upgrade→Upgrade (during the upgrade process, the USB cannot be pulled out, and the USB will be automatically read after the upgrade is completed)

The upgrade process cannot be powered off, pay attention to whether the file name of the U disk is correct, and confirm the version information before upgrading.

1. The original car has a black screen, and a black screen is installed -----1. Check whether the LVDS cable is connected correctly, and eliminate the problem of poor LVDS contact; 2. If the above problems cannot be eliminated, check whether the dialing code is correct.

2. The display of the original car is normal and the operation of the knob is normal. If the display is overflowing or dissatisfied, the screen is black or blurred or the screen is flickering, check whether the dialing code of the decoder is correct and whether the LVDS cable is plugged in properly.

3. The sound of the original car is normal, but CarPlay has no sound. ----CarPlay sound channel is selected as the original car AUX

4. There is an echo on the phone (outside the car)-----In the setting item, press the echo cancellation method to eliminate.

5. There is no sound in CarPlay music or calling the car - check whether the sound is in the AUX channel, do not connect the original car Bluetooth or mobile phone to see if the current channel status of the music is in the CarPlay channel.

6. CarPlay has been connected to display a black screen, and the sound is normal - turn off the mobile phone WIFI and BT, and see if the installation interface can be displayed normally. If it cannot be ruled out, press and hold the next button of the original car for 10 seconds to restart the CarPlay system.

7. CarPlay freezes when playing music or the navigation does not refresh - check whether the network on the mobile phone is normal and whether the decoder antenna is tightened.

8. CarPlay cannot be connected automatically ---- Check whether the Bluetooth and WIFI on the mobile phone are turned on. If they are turned on click IOS to connect again.

9. CarPlay SiRi has no effect ------ Check if the audio MIC is set to the original car, it needs to be turned off

10.The knob has no effect-----Confirm whether the small board cable is installed properly, and do not insert it crookedly. After the knob is installed confirm that the original car is turned off and the power cord is turned on.

11. Reversing on the installation interface does not switch the screen ---- check if the CAN cable of the air conditioner panel is connected well) After the connection, it needs to be connected with the 2G40 power cable (two aircraft buckle plugs), if it still does not work, check whether the dial code corresponds to .

12. MIC has no effect ---- enter the installation setting interface and set it to install MIC

合 格 證
CERTIFICATE

產品名稱:
Product name

規格型號:
Model

出廠日期:
leave factory date

檢 驗 員:
Inspectror

QC
PASS
廠02

生產廠家:
Manufacturer

本產品經檢驗符合規定
的質量標準，准予出廠
This product meets the
requirements after inspection
The quality standard, allowed
to leave the factory